

PVC SOLVENT CEMENT, PRESSURE

Bostik PVC Pipe Cement Pressure

Product	Bostik PVC Pipe Cement Pressure
Manufacturer	Bostik Australia Pty Ltd
Where 6D uses it	Welding cement for uPVC pressure pipe.
Signal word	Danger
Classification	Flammable liquids Cat 2; Acute toxicity oral, dermal and inhalation Cat 4; Skin corrosion or irritation Cat 2; Serious eye damage Cat 1; Carcinogenicity Cat 2; STOT single exposure Cat 3
Pictograms	GHS02, GHS05, GHS07, GHS08
Dangerous goods	UN 1133, Class 3, PG II
Poisons schedule	Not stated on the sheet
Manufacturer's sheet	22 November 2017, version 1.01. 9 pages.
Review due	22 November 2022

FIRST AID, FROM SECTION 4 OF THE MANUFACTURER'S SHEET

Inhalation: Remove to fresh air.

Skin: Wash with plenty of soap and water.

Eyes: In case of contact with eyes, rinse immediately with plenty of water and seek medical.

Swallowed: If swallowed, do not induce vomiting: seek medical advice immediately and show this.

Emergency 000. Poisons Information Centre 13 11 26.



Scan for the current sheet

6dcivil.com.au/sds/bostik-pvc-pipe-cement-pressure

The website copy is the current one. A printed sheet is uncontrolled and may have been superseded since it was printed.

This cover is 6D Civil's summary of the manufacturer's safety data sheet, which follows this page and governs. Register 6DC-OHS-RG-0004 Rev A. Section 330(3) of the Work Health and Safety Regulation 2011 (Qld) requires the manufacturer or importer of a hazardous chemical to review its safety data sheet at least once every five years, and to amend it whenever necessary to keep it correct and current.

BOSTIK PVC PIPE CEMENT PRESSURE
 Revision Number 1.01

Revision Date 22-Nov-2017
 Supersedes Date: 22-Nov-2018

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier

Product Name BOSTIK PVC PIPE CEMENT PRESSURE
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives.
Uses advised against No information available.

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik New Zealand Limited
 19 Eastern Hutt Road Wingate,
 Lower Hutt, New Zealand
 Tel: 04-567 5119
 Fax: 04-567 5412

1.4. Emergency telephone number

Emergency Telephone 24 Hr: 0800 243 622
 +64 4 917 9888
 Poison Centre : 0800 764 766

E-mail address SDS.AP@Bostik.com

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Acute toxicity - Oral	Category 4 (6.1D)
Acute toxicity - Dermal	Category 4 (6.1D)
Acute toxicity - Inhalation (Vapors)	Category 4 (6.1D)
Acute toxicity - Inhalation (Dusts/Mists)	Category 4 (6.1D)
Skin corrosion/irritation	Category 2 (6.3A)
Serious eye damage/eye irritation	Category 1 (8.3A)
Carcinogenicity	Category 2 (6.7B)
STOT - single exposure	Category 3 (f)
Flammable Liquids	Category 2 (3.1B)

Classification in parenthesis is applicable for New Zealand Hazard Classification

ERMA Group HSR002669

2.2. Label Elements



Signal word DANGER

Hazard statements

Safety Data Sheet

BOSTIK PVC PIPE CEMENT PRESSURE
Revision Number 1.01

Revision Date 22-Nov-2017
Supersedes Date: 22-Nov-2018

H302 - Harmful if swallowed
H312 - Harmful in contact with skin
H315 - Causes skin irritation
H318 - Causes serious eye damage
H332 - Harmful if inhaled
H335 - May cause respiratory irritation
H351 - Suspected of causing cancer
H225 - Highly flammable liquid and vapor

Precautionary Statements - Prevention

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P281 - Use personal protective equipment as required
P264 - Wash face, hands and any exposed skin thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray
P271 - Use only outdoors or in a well-ventilated area
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical/ ventilating/ lighting/ equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P235 - Keep cool

Precautionary Statements - Response

P321 - Specific treatment (see supplemental first aid instructions on this label)

Inhalation

P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Skin

P312 - Call a POISON CENTER or doctor if you feel unwell
P332 + P313 - If skin irritation occurs: Get medical advice/attention
P303 + P361 + P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P363 - Wash contaminated clothing before reuse

Eyes

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor/physician

Ingestion

P301 + P312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
P330 - Rinse mouth

Fire

In case of fire: Use CO2, dry chemical, or foam to extinguish

Precautionary Statements - Storage

P405 - Store locked up
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other Hazards

Safety Data Sheet

BOSTIK PVC PIPE CEMENT PRESSURE
Revision Number 1.01

Revision Date 22-Nov-2017
Supersedes Date: 22-Nov-2018

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Mixture

3.2 Mixtures

Chemical Name	CAS No.	Weight-%
Cyclohexanone	108-94-1	40 - <80
Tetrahydrofuran	109-99-9	40 - <80
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	25068-38-6	0.1- <1

*** Any remaining ingredients are not hazardous

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

General advice	If medical advice is needed, have product container or label at hand.
Inhalation	Remove to fresh air.
Skin contact	Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.
Eye contact	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
Ingestion	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.
Self-protection of the first aider	Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	None known.
----------	-------------

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians	Treat symptomatically.
--------------------	------------------------

4.4. Reference to Other Sections

Reference to other sections	See Section 12: ECOLOGICAL INFORMATION. Section 7: HANDLING AND STORAGE. Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.
-----------------------------	--

Section 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media	Use CO2, dry chemical, or foam.
------------------------------	---------------------------------

Unsuitable extinguishing media	No information available.
--------------------------------	---------------------------

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).
--	--

5.3. Advice for firefighters

Safety Data Sheet

BOSTIK PVC PIPE CEMENT PRESSURE
Revision Number 1.01

Revision Date 22-Nov-2017
Supersedes Date: 22-Nov-2018

Special protective equipment for fire-fighters Wear self contained breathing apparatus for fire fighting if necessary.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas.
Other information	Water spray may reduce vapor; but may not prevent ignition in closed spaces.
For emergency responders	Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2. Environmental precautions

Environmental precautions	Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Methods for containment	Dike far ahead of spill; use dry sand to contain the flow of material. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).
Methods for cleaning up	Use clean non-sparking tools to collect absorbed material. Dike far ahead of spill for later disposal.

6.4. Reference to other sections

Reference to other sections	See Section 12: ECOLOGICAL INFORMATION Section 7: HANDLING AND STORAGE Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION
------------------------------------	---

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling	Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Take precautionary measures against static charges. Use explosion-proof electrical/ ventilating/ lighting/ equipment.
--------------------------------	--

7.2. Conditions for safe storage, including any incompatibilities

General hygiene considerations	Do not eat, drink or smoke when using this product. Regular cleaning of equipment, work area and clothing is recommended.
Storage Conditions	Keep only in the original container/package in a cool well-ventilated place. Protect from moisture.
Incompatible materials	Strong acids and bases

7.3. Specific end use(s)

Other information	No information available.
--------------------------	---------------------------

7.4. References to Other Sections

Reference to other sections	See Section 12: ECOLOGICAL INFORMATION. Section 7: HANDLING AND STORAGE. Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.
------------------------------------	--

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Safety Data Sheet

BOSTIK PVC PIPE CEMENT PRESSURE
Revision Number 1.01

Revision Date 22-Nov-2017
Supersedes Date: 22-Nov-2018

8.1. Control parameters

Exposure Limits

This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies

Chemical Name	New Zealand	Australia	European Union
Cyclohexanone 108-94-1	TWA: 25 ppm TWA: 100 mg/m ³ Skin	25 ppm TWA 100 mg/m ³ TWA	TWA: 10 ppm TWA: 40.8 mg/m ³ STEL: 20 ppm STEL: 81.6 mg/m ³ *
Tetrahydrofuran 109-99-9	TWA: 100 ppm TWA: 295 mg/m ³ Skin	100 ppm TWA 295 mg/m ³ TWA	TWA: 50 ppm TWA: 150 mg/m ³ STEL: 100 ppm STEL: 300 mg/m ³ *

Chemical Name	ACGIH TLV	NIOSH IDLH	OSHA PEL
Cyclohexanone 108-94-1	STEL: 50 ppm TWA: 20 ppm S*	IDLH: 700 ppm TWA: 25 ppm TWA: 100 mg/m ³	TWA: 50 ppm TWA: 200 mg/m ³
Tetrahydrofuran 109-99-9	STEL: 100 ppm TWA: 50 ppm S*	IDLH: 2000 ppm TWA: 200 ppm TWA: 590 mg/m ³ STEL: 250 ppm STEL: 735 mg/m ³	TWA: 200 ppm TWA: 590 mg/m ³

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration (PNEC) No information available

OTHER INFORMATION No information available

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

PPE - Personal Protection Equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin and body protection	Wear suitable protective clothing. No special technical protective measures are necessary under normal conditions.
Hand protection	Wear suitable chemical resistant gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality and various manufacturers.
Respiratory protection	No protective equipment is needed under normal use conditions. Respiratory protection required in insufficiently ventilated working areas and during spraying. An air-fed mask, or for short periods of work, a combination of professional filter is recommended.
General hygiene considerations	Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Avoid contact with skin, eyes or clothing. Take off contaminated clothing and wash before reuse.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Color	Clear, colorless
Odor	Solvent
Odor Threshold	No information available

Safety Data Sheet

BOSTIK PVC PIPE CEMENT PRESSURE
Revision Number 1.01

Revision Date 22-Nov-2017
Supersedes Date: 22-Nov-2018

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	
Melting point / freezing point	No information available	
Boiling point / boiling range	approx. 66 °C / 150.8 °F	
Flash Point	approx. -15 °C / 5 °F	
Evaporation Rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability or explosive limits	10.9	
Lower flammability or explosive limits	1.7	
Vapor Pressure	No information available	
Vapor Density	No information available	
Relative Density	No information available	
Water Solubility	Partially soluble	
Solubility in Other Solvents	No information available	
Partition coefficient	No information available	
Autoignition Temperature	321 °C / 609.8 °F	
Decomposition Temperature	No information available	
Kinematic Viscosity	No information available	
Dynamic Viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	
<u>9.2. Other information</u>		
Softening Point	No information available	
Molecular Weight	No information available	
Solvent content (%)	No information available	
Solid content (%)	approx. 15	
Density		1.0 g/cm ³
Bulk Density	No information available	
VOC (volatile organic compound)	> 300 g/L	

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

Reactivity Stable under recommended storage conditions.

10.2. Chemical stability

Stability Stable under recommended storage conditions

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Hazardous Polymerization None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Keep away from heat, sparks and flames. Protect from moisture.

10.5. Incompatible materials

Incompatible materials Strong acids and bases.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions.

Section 11: TOXICOLOGY INFORMATION

Safety Data Sheet

BOSTIK PVC PIPE CEMENT PRESSURE
Revision Number 1.01

Revision Date 22-Nov-2017
Supersedes Date: 22-Nov-2018

11.1. Information on toxicological effects

Acute Toxicity

Product information	Product does not present an acute toxicity hazard based on known or supplied information.
Inhalation	No data available.
Eye contact	No data available.
Skin contact	No data available.
Ingestion	No data available.

Numerical measures of toxicity

Unknown acute toxicity

3E-06 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
40.020943 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
84.434943 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
40.020943 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
40.020943 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Cyclohexanone 108-94-1	= 1535 mg/kg (Rat)	= 947 mg/kg (Rabbit)	= 8000 ppm (Rat) 4 h
Tetrahydrofuran 109-99-9	= 1650 mg/kg (Rat)	-	= 21000 ppm (Rat) 3 h
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW 25068-38-6	LD50 (rat) > 2000 mg/kg OECD 420	>2000 mg/Kg (rat)	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	No information available.
Serious eye damage/eye irritation	No information available.
Sensitization	No information available.
Germ Cell Mutagenicity	No information available.
Reproductive Toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Target Organ Effects	Central nervous system, Eyes, Kidney, Liver, Respiratory system, Skin.
Aspiration hazard	No information available.
Carcinogenicity	The following substance(s) are classified in Annex VI CLP (1272/2008) as carcinogenic.

Chemical Name	IARC	China	Japan
Cyclohexanone	Group 3	-	-
Tetrahydrofuran	Group 2B	-	-
IARC (International Agency for Research on Cancer)		Group 3 - Not Classifiable as to Carcinogenicity in Humans	

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity

Product information

None known.

Component Information

Data obtained on the component(s) include

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Cyclohexanone	EC50: =20mg/L (96h, Chlorella)	LC50 96 h 481 - 578 mg/L	EC50: =800mg/L (24h, Daphnia)

Safety Data Sheet

BOSTIK PVC PIPE CEMENT PRESSURE
Revision Number 1.01

Revision Date 22-Nov-2017
Supersedes Date: 22-Nov-2018

108-94-1	vulgaris)	(Pimephales promelas flow-through)	magna)
Tetrahydrofuran 109-99-9	-	LC50: 2700 - 3600mg/L (96h, Pimephales promelas) LC50: 1970 - 2360mg/L (96h, Pimephales promelas)	EC50: =5930mg/L (24h, Daphnia magna)
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW 25068-38-6	EC50 (72h) = 9.4 mg/L (Scenedesmus capricornutum) EPA-660/3-75-009	1.2 mg/l 96Hr (Oncorhynchus mykiss)	2.7 mg/l 48hr Daphia Magna

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

Chemical Name	Partition coefficient	Bioconcentration factor (BCF)
Cyclohexanone 108-94-1	0.86	-
Tetrahydrofuran 109-99-9	0.45	-
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW 25068-38-6	3.26	31

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

Chemical Name	PBT and vPvB assessment
Cyclohexanone 108-94-1	The substance is not PBT / vPvB PBT assessment does not apply
Tetrahydrofuran 109-99-9	The substance is not PBT / vPvB PBT assessment does not apply
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW 25068-38-6	The substance is not PBT / vPvB

12.6. Other adverse effects

No information available.

Endocrine Disruptor Information

Chemical Name	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Endocrine disrupting potential
Tetrahydrofuran	Group III Chemical	-	-
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	Group III Chemical	-	-

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from residues/unused products

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging

Improper disposal or reuse of this container may be dangerous and illegal.

Section 14: TRANSPORT INFORMATION

Safety Data Sheet

BOSTIK PVC PIPE CEMENT PRESSURE
Revision Number 1.01

Revision Date 22-Nov-2017
Supersedes Date: 22-Nov-2018

IMDG

UN Number	UN1133
Proper Shipping Name	Adhesives
Transport hazard class(es)	3
Packing Group	II
EmS-No.	F-E, S-D
Limited Quantity (LQ)	5 L
Description	UN1133, Adhesives, 3, II, (-15°C c.c.)

IATA

UN Number	UN1133
Proper Shipping Name	Adhesives
Transport hazard class(es)	3
Packing Group	II
ERG Code	3L
Limited Quantity (LQ)	1 L
Special Provisions	A3
Description	UN1133, Adhesives, 3, II

ADR

UN Number	UN1133
Proper Shipping Name	Adhesives, Environmentally Hazardous
Transport hazard class(es)	3
Labels	3
Packing Group	II
Description	UN1133, Adhesives, Environmentally Hazardous, 3, II, (D/E)
Environmental hazards	Yes
Limited Quantity (LQ)	5 L
Special Provisions	640C
Classification Code	F1
Tunnel Restriction Code	(D/E)

Section 15: REGULATORY INFORMATION

National Regulations

Section 16: OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet

No information available

Key Literature References and Sources for Data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision Date 22-Nov-2017

Revision note Not applicable.

Training Advice Provide adequate information, instruction, and training for operator

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet